



Laser RangeFinder

Specifications:

Dimensions:	5" x 2" x 3.5" (12 cm x 5 cm x 9 cm)
Weight:	8 ounces (220 g)
Data communication:	Serial, via wired RS232 (standard) or wireless Bluetooth® (optional with 200B model) Class 2 device, compliant with Bluetooth Specification 1.1 and configured with the Serial Port Protocol (SPP).
Power:	3.0 volts DC nominal; (2) AA batteries (Alkaline, NiCd/NiMH, Lithium) or (1) CRV3 battery
Battery duration:	AA - approx. 7500 measurements (6000 with Bluetooth® enabled); CRV3 – approx. 15,000 measurements (12,000 with Bluetooth® enabled)
Eye safety:	FDA Class 1 (CFR 21)
Environmental:	Impact, water and dust resistant; NEMA 3, IP 54
Temperature:	-4°F to +140°F (-20°C to +60°C)
Optics:	7X magnification (field of view: 330 ft @ 1000yds)
Display:	In-scope LCD
Units:	Feet, Yards, Meters, and Degrees
Mount:	Monopod/tripod (1/4" - 20 thread)

Measurement Range:

- Distance: 0 to 3280 ft (1000 m) typical; 6560 ft (2000 m) max to reflective target
- Inclination: +/- 90 degrees

Accuracy:

- Distance: +/- 1 ft (+/- 30 cm), high quality target
+/- 1 yd (+/- 1 m), low quality target
- Inclination: +/- 0.25 degrees

Measurement Modes / Features:

- Horizontal distance, vertical distance, slope distance and inclination measurements
- 3-point flexible height routine with auto sequencing
- Advanced target modes: Closest, Farthest, Continuous, Filter (reflector only)
- TruTargeting: Automatically provides the best possible accuracy and acquisition distance to a given target.

Contact Us for further information on this product.

